


## Oval Conduit Product Data Sheet

Product Range	EC016, EC017, EC018, EC019 & EC020	<p>Image for reference only</p> 
Description	PVCu Oval Conduit	
Key Features	Light Gauge Range of fittings Operating Temperature -5°C to +60°C Non-Flame Propagating to BS EN 61386-1 High Impact Resistance to -5°C Heavy Gauge Requirements of BS EN 61386-1	
Dimensions	13 x 8mm, 16 x 10mm, 23 x 11mm 29 x 11mm & 32 x 11mm	
Material(s)	PVCu (White only)	
Compliance / Standards(s)	CE & UKCA Marked Low Voltage Directive 2014/35/EU The Electrical Equipment (Safety) Regulations 2016 BS 7671:2018 BS EN 61386-1:2008+A1:2019 BS EN 60386-21:2004+A11;2010 BS 4607-1:1984+A2:2010 BS 4607-5:1982+A3:2010	
Packaging	Recyclable	

### Sustainability

We work hard to ensure our products meet the highest standards and are totally committed to the environment and maximising our usage of recycled material within our manufacturing process.

Our PVC-U products are manufactured from an average of 80% recycled plastic, with some extruded products produced from 100% recycled material.

Oval Conduit is manufactured from PVC-U, a material that is 100% recyclable, is flame retardant and self-extinguishing.

- To find out more about the percentage of recycled material used in this product, please visit [marshall-tufflex.com](http://marshall-tufflex.com)

