

Power Floor Grommet Product Data Sheet

Product Range	UPG1 & UPG2	Image for reference only 
Description	Raised Floor Grommet (with foam insert)	
Key Features	<p>Supplied with 1 Gang 13A DP Socket outlet</p> <p>Integrated lid locking screw</p> <p>Quick installation</p> <p>Adjustable lid can be set to meet optimum cable requirement, minimising air leakage through the opening</p> <p>Can be used with flexible cable and Flexible conduit.</p> <p>Black (RAL9004) or Grey (RAL7037)</p>	
Dimensions	<p>Floor Cut-out Ø125</p> <p>Overall diameter Ø140</p> <p>Depth 87mm (including accessory box)</p>	
Material(s)	<p>ABS Flame Retardant and Galvanised Steel</p> <p>Nitrile foam insert</p>	
Compliance / Standards(s)	<p>CE & UKCA Marked</p> <p>Low Voltage Directive 2014/35/EU</p> <p>The Electrical Equipment (Safety) Regulations 2016</p> <p>BS 7671:20018</p> <p>BS EN 61534-1:2011</p> <p>BS EN 61534-22:2009</p> <p>All Plastics are UL94-V0 rated and pass IEC 60695-2 glow wire test at 850°C</p>	
Packaging	Recyclable	

Sustainability

We work hard to ensure our products meet the highest standards and are totally committed to the environment and maximising our usage of recycled material within our manufacturing process.

Grommets are manufactured from 100% recyclable materials all offering excellent fire performance.

